




5P~15P



2P~5P



TECHNICAL CHARACTERISTICS

MATERIAL
 INSULATOR: NYLON 66
 FLAMABILITY RATING: UL94-V0
 COLOR: GREY
 PITCH: 1.50MM

ENVIRONMENTAL
 OPERATING TEMPERATURE: -25 UP TO 85°C
 COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL
 INSULATOR RESISTANCE: >100 MOHM
 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC/MN

STANDARD
 CERTIFIED: E323964


PACKAGING
 BAG

DIMENSION
 A = 1.50 x (NB. PIN - 1)
 B = 1.50 x (NB PIN) + 0.30
 C = 1.50 x (NB PIN + 1)

RoHS Compliant

G	07-AUG-13	CHARACTERISTIC	QL
F	26-OCT-11	DRAWING	JC
E	17-NOV-09	STANDARD	JP
D	28-OCT-09	INSULATOR R.	JP
C	01-FEB-07	DRAW	EC
B	31-MAR-04	LEAD FREE	JP
A	04-SEP-98	PDF	JP
REV	DATE	FILE	BY

PROJECTION:



GENERAL TOLERANCE
 .X = +/- 0.2
 .XX = +/- 0.15



APPROVAL: RJ

UNIT: MM
 SCALE:
 SHEET: 1/1
 DRAW: PEARL

DESCRIPTION: 1.50 MM FEMALE TERMINAL HOUSING
 WERI PART NO: 6480xx113322

SIZE
A4